



P.C.B LAYOUT

No. of Contact	A	B	C	D
15 Pin	±0.25	±0.13	±0.38	±0.25
26 Pin	16.92	24.99	30.81	19.28
44 Pin	25.25	33.32	39.14	27.51
62 Pin	38.96	47.04	53.04	41.28
	55.42	63.50	69.32	57.71

MATERIALS AND FINISH

SHELL : STEEL MATERIAL, FRONT NICKEL FINISHED
 BACK SHELL TIN FINISHED
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED, UL 94V-0 RATED, WHITE COLOR
 CONTACT MATERIAL : BRASS
 CONTACT FINISH : FULL GOLD FINISHED

ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS
 CONTACT RESISTANCE : 30 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
 TEMPERATURE RATING : -55°C ~ +105°C

Drawn by	2010.05.10	D-SUB Connector, Machined Pin, H.D. R/A Dip Type, 8.89MM Footprint, Male
Designed by	2010.05.10	
Approved by	2010.05.10	
Sheet 1 of 1	Code 000	
Dimensions in mm(inches)	Scale 1:1	Ver A0
Tolerances on:XX+/-0.13	Angles+/-2°	